

# **DIRECTA**

## **ESSENTIALS FOR INDUSTRY**

Tel: 01621 828882

[www.directa.co.uk](http://www.directa.co.uk)

### **TECHNICAL DATA SHEET**

**PRODUCT:** Tork Premium Specialist Cloth

Our Ref: M90492

### **PRODUCT FEATURES**

#### **Benefits**

- A low linting and very strong cloth in dispenser bucket

### **SHIPPING**

#### **Consumer Unit Specifications**

Pcs/Con: 1

Gross weight/con: 1.1595 kg

Net weight/con: 0.9555 kg

Packaging: Plastic bucket

EAN Con: 7322540297973

#### **Transport unit specifications**

Packaging trp: Carton

Con/Trp: 4

Length, trp: 478 mm

Width, trp: 238 mm

Height, trp: 403 mm

Volume, trp: 0.04585 m<sup>3</sup>

Gross weight, trp: 5.238 kg

Net weight/trp: 3.822 kg

Ean trp: 7322540297997

#### **Tork Premium Specialist Cloth Precision Cleaning Roll in Bucket**

17.5 cm 70 m

**Article #** 90492

**System** W10-Handy Bucket

**Color** Turquoise

**Print** No

**Roll length** 70 m

**Roll width** 17.5 cm

**Sheets** 250

Pcs Trp: 4

Trp Pallet: 30

### **ENVIRONMENT**

#### **Content**

Chemical pulp

Polyester

Chemicals

## **Material**

### **Chemical pulp**

Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free). ECF is based on oxygen, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.

### **Polyester**

Polyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length.

### **Chemicals**

Both functional and process chemicals are used. The functional chemical used is wet strength agent. The wet strength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre. Process chemical used is a surfactant.

This product is produced externally in DE.

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.

DS561.TDS

26<sup>th</sup> August 2009