



Technical Data Sheet

Product Code:	FL219. POLYETHYLENE TAPE
----------------------	--------------------------

DESCRIPTION

This product is recommended for the protection of sensitive surfaces against dirt and damage during processing, storage and mounting e.g. carpet

PREPARATION

Ensure surfaces to be treated are free from grease, solvents, dust and loose material.

TECHNICAL PROPERTIES

Carrier	Polyethylene
Adhesive	Acrylic
Average Thickness	45 Micron
Peel adhesion to Stainless Steel	5N±1/25mm
Breaking Strength Machine Direction (MD)	>70N/25mm
Breaking Strength Transverse Direction (TD)	>62.5N/25mm
Elongation at break Machine Direction (MD)	400%
Elongation at break Transverse Direction (TD)	450%
Shelf life	6 months when stored in original packaging in cool dry conditions.

ADDITIONAL INFORMATION

All the information in this data sheet is published in good faith and is intended to serve as a guide only. As we have no control over the manner or conditions in which our products are used, we cannot accept liability for results. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. Responsibility for ascertaining the suitability of products for the user's purposes rests with the purchaser.

Directa UK Limited and its agents cannot assume liability or responsibility for their requirements and adopt such precautions as required for the protection of personnel and property in the handling and usage of Directa UK Limited materials