DIRECTA
ESSENTIALS FOR INDUSTRY
Tel: 01621 828882 www.directa.co.uk

TECHNICAL DATA SHEET

PRODUCT: Barrier Tape Our Reference: 08724COHT / 08723COHT

TECHNICAL DETAILS:

70mm x 500M x 0.22mu thick Barrier Tape, manufactured from high quality, virgin grade, corona treated, lead-free masterbatch coloured LDPE.

Colour: Red/White striped / Yellow/Black striped

Single wound sheet

Low Slip

INSTRUCTIONS/USES:

Used for temporary cordoning of hazardous areas and marking out incident scenes, racecourses, car parks etc.

SPECIFICATION:

Tolerances on Dimensions:

Length: +/-2.5% Width at Weld: +/ -2.5$ Open Width: +/2,5%

PERFORMANCE REQUIREMENTS:

Dart Impact:	All areas 120gf	
Elmendorf Tear Resistance:	Four thicknesses should average not less than:	Lengthways 180mN Widthways 270mN

Tensile strength:	Lengthways 15N 200% Elongation Widthways 14N 350% Elongation	Centre Weld 11N

All the above information is given in good faith, but the figures are typical values only and should not be taken as a guarantee of performance. Manufacturing tolerances for dimensional and technical characteristics apply and are available on request. The company reserves the right to improve the product and adjust the specification without notice.