

TECHNICAL DATASHEET

Painters low tack UV resistant Masking Tape

PRODUCT CODE: 20003AUBU and 20003BSBU

DESCRIPTION

Fine structured crepe (FSC) paper tape coated with a UV resistant Solventless Acrylic adhesive system.

APPLICATIONS

Professional painters and plasterers masking tape.
Suitable for brush, roller and spray applications.

ADVANTAGES

Can be used outside with 14 day clean removal.
Smooth and controlled unwind.
Good peel adhesion.
Good shear and holding strength.
Good paint flake resistance.
No staining.
Good Humidity resistance.
Resistant to mild chemicals, lacquers, solvents and water.

<u>Technical Properties</u>	<u>Value</u>	<u>Unit</u>
Carrier Thickness	80 ± 15	micron
Total Thickness	110 ± 25	micron
Adhesive Coat Weight	25	gr/m ²
Elongation at Break MD	10	%
Peel Adhesion	2.4	N/in
Rolling Ball Tack	5	cm
Temperature Resistance	60	° C

Important

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. Directa and its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products. Sellers & Manufacturers only obligation shall be to replace the product proven to be defective.