



## **Technical Data Sheet**

<b>Product Code:</b>	166 HIGH PERFORMANCE EXTRUDED CLOTH TAPE
----------------------	--

### **DESCRIPTION**

166 is an extruded polyethylene cloth tape with a pressure sensitive high tack rubber adhesive. The product displays high conformability and adhesion over a wide temperature range, (recommended service temperature 0 Degrees to +40 Degrees Centigrade) which makes it excellent for most industrial duct applications. Easily torn by hand.

### **PREPARATION**

Ensure surfaces to be treated are free from grease, dust and loose material.

### **TECHNICAL PROPERTIES**

Carrier	Extruded polyethylene/cloth
Adhesive	Natural rubber based
Thickness	240 Micron $\pm$ 10 Micron
Peel Adhesion (180°)	10.8N/25mm
Ball tack no. (typical)	23
Tensile Strength	108N/25mm
Elongation @ break	12%
Unwinding force	6.7N/25mm
Shelf life	1 year if stored in original packaging in cool dry conditions out of direct sunlight

### **ADDITIONAL INFORMATION**

All the information in this data sheet is published in good faith and is intended to serve as a guide only. As we have no control over the manner or conditions in which our products are used, we cannot accept liability for results. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. Responsibility for ascertaining the suitability of products for the user's purposes rests with the purchaser.

Directa UK its agents cannot assume liability or responsibility for their requirements and adopt such precautions as required for the protection of personnel and property in the handling and usage of Directa UK Limited materials.