

### DEEMARK ANTI SLIP TAPE

Ref - 084

Ref	DS100
Date	Dec 2014
Pages	1 of 1

#### DESCRIPTION

Premium quality, self-adhesive, non-slip tape with an abrasive surface to help reduce the risk of slips and falls.

Made from a tough, waterproof PVC base impregnated with aluminium oxide crystals.

#### INSTRUCTIONS / USES

Creates a non-slip surface for steps, stairs, ramps and slippery surfaces.

**INSTALLATION :** Apply in temperatures of not less than 5°C, ensuring the surface is clean, dry and free from dust, grease, oil or other contaminants. Apply a brushed coating of UKT79 Primer to the ground surface and allow to almost dry. Remove the backing paper and unroll the tape, applying even pressure to ensure a firm bond. Pay particular attention to the edges of the tape. For best results, a bead of UKT79 Edge Sealer should be applied along the exposed edges. Allow at least one hour (preferably 24 hours) before walking/driving over the tape.

#### BENEFITS / KEY FEATURES

- > Premium quality
- > Tough, durable and long-lasting
- > High level of "Coefficient of Friction" (the accepted measurement of non-slip grip)
- > Will adhere to most surfaces

#### STANDARD VERSIONS

PLAIN COLOURS			STRIPED COLOURS
Black	Hi Viz Yellow	Grey	Black & Yellow Red & White
Transparent	Dull Yellow	Orange	
White	Blue	Brown	
Red	Green		
TAPE WIDTHS			ROLL LENGTH
25mm	100mm	300mm	18M long
50mm	150mm	450mm	
75mm	200mm		

#### TECHNICAL INFORMATION

<b>TAPE THICKNESS</b>	<b>ADHESIVE</b>	<b>CORE</b>
700mu (0.70mm) excluding liner	Solvent Acrylic	76mm diameter cardboard core
<b>ELONGATION</b>	<b>TENSILE STRENGTH</b>	<b>ADHESION TO STEEL</b>
25%	6 Kg /25mm <sup>2</sup>	1.5 Kg /25mm <sup>2</sup>
<b>RESISTANCE TO WATER</b>	<b>RESISTANCE TO CHEMICALS</b>	<b>TEMPERATURE RANGE</b>
10 months (PSTC-35)	8 months (PSTC-35)	-30°C to +70°C
<b>COEFFICIENT OF FRICTION</b>	<b>COEFFICIENT OF FRICTION</b>	<b>ROLL WEIGHT</b>
98 (Dry surface)	68 (Wet surface)	0.80 Kgs (based on 50mm x 18M)