

DIRECTA

ESSENTIALS FOR INDUSTRY SINCE 1971

Tel: 01621 828882 Email: sales@directa.co.uk
www.directa.co.uk

Deemark Anti Slip Tape Ref: 084



DESCRIPTION

Premium quality, self-adhesive, non-slip tape with an abrasive surface to help reduce the risk of slips and falls. Made from a tough, waterproof PVC base impregnated with aluminium oxide crystals. Creates a non-slip surface for steps, stairs, ramps and slippery surfaces.

INSTRUCTIONS / USES

INSTALLATION : Apply in temperatures of not less than 5°C, ensuring the surface is clean, dry and free from dust, grease, oil or other contaminants. Apply a brushed coating of UKT79 Primer to the ground surface and allow to almost dry. Remove the backing paper and unroll the tape, applying even pressure to ensure a firm bond. Pay particular attention to the edges of the tape. For best results, a bead of UKT79 Edge Sealer should be applied along the exposed edges. Allow at least one hour (preferably 24 hours) before walking/driving over the tape.

BENEFITS / KEY FEATURES

- > Premium quality
- > Tough, durable and long-lasting
- > High level of "Coefficient of Friction" (the accepted measurement of non-slip grip)
- > Will adhere to most surfaces

STANDARD VERSIONS		
PLAIN COLOURS		STRIPED COLOURS
Black	Hi Viz Yellow	Grey
Transparent	Dull Yellow	Orange
White	Blue	Brown
Red	Green	
TAPE WIDTHS		ROLL LENGTH
25mm	100mm	300mm
50mm	150mm	450mm
75mm	200mm	18M long
TECHNICAL INFORMATION		
TAPE THICKNESS	ADHESIVE	CORE
700mu (0.70mm) excluding liner	Solvent Acrylic	76mm diameter cardboard core
ELONGATION	TENSILE STRENGTH	ADHESION TO STEEL
25%	6 Kg /25mm ²	1.5 Kg /25mm ²
RESISTANCE TO WATER	RESISTANCE TO CHEMICALS	TEMPERATURE RANGE
10 months (PSTC-35)	8 months (PSTC-35)	-30°C to +70°C
COEFFICIENT OF FRICTION	COEFFICIENT OF FRICTION	ROLL WEIGHT
98 (Dry surface)	68 (Wet surface)	0.80 Kgs (based on 50mm x 18M)