


Topper General Purpose Masking Tape

200GPAIBU	12mm x 50M
200GPAUBU	24mm x 50M
200GPBGBU	36mm x 50M
200GPBSBU	48mm x 50M
200GPCQBU	72mm x 50M
200GPDMBU	96mm x 50M



Product Description

Entry Level, medium/high adhesion masking tape characterized by a thin crepe paper backing and a synthetic rubber resin solvent free adhesive. Suitable for indoor light duty applications, for non-critical masking and painting operations, and for general bundling, holding, splicing, and labeling.

It is recommended to use at room temperature.

Features

- Thin paper for general masking operations
- Excellent quality price ratio
- Good contact on multiple surfaces
- Good paint anchorage
- Indoor removal time: 1 Day

Main Applications

- Light duty painting operations (no UV exposure recommended)
- Non - critical bundling, splicing and holding
- General labeling and marking activities

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	75 g/m ²	75 g/m ²	ISO 536
Total thickness*	97 µm	3.8 mils	Internal
MD tensile strength*	36 N/cm	20.6 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	7 %	7 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	4.2 N/cm	38.4 oz/in	AFERA 5001/PSTC 101

Backing material
Saturated crepe paper

Type of adhesive
Synthetic rubber resin - solvent free

*Typical value

Available colour



White Yellow

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. Directa UK Ltd reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. Directa UK Ltd does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.